



Code review 小结 2015-08-14

作者是哪位大神?

- commit 2349ae927d410735d67be27db4377daa4338b5b0
- Author: admin <admin@happysoft.cc>
- Date: Thu Aug 13 10:49:34 2015 +0800
- 使用 HTTParty 发送短信给客户

这句话的意思?

- commit e890a8cdb97149dd1a57cc0aa9f3753122e26546
- Author: 黄敏 <huangmin0822@163.com>
- Date: Wed Aug 12 15:26:06 2015 +0800
- 分享不能到 APP store 的提示

163.com, live.com 开源项目?

- commit ffbcbb51c73965c2aca9257a34f50a83fb8ef418
- Author: 黄敏 <huangmin0822@163.com>
- Date: Mon Aug 10 11:32:11 2015 +0800
- 灵感, 发现, 管理相关的默认值, 下拉框选择及搜索
- commit b211dad18d7902ee9ad10b8c739363669621d79b
- Author: dwgeneral <guowind@live.com>
- Date: Fri Aug 7 19:50:04 2015 +0800
- 将路径又换回了相对路径

Git 小技巧

`.git/config`（针对某个目录）和 `~/.gitconfig`（针对某个用户）文件是配置文件，

里面可以设置 用户名， `email`， 例如：

```
$ cat ~/.gitconfig
```

```
[user]
```

```
email = shensiwei@happysoft.cc
```

```
name = siwei
```

```
[core]
```

```
editor = vim
```

调整了哪里的样式？ 它跟“修改代码”的几乎
作用一样。

- `commit 43335db063f36cb726c7467540b4528d1b4115bd`

Date: Wed Aug 5 10:07:09 2015 +0800

- 调整样式

Gemfile, 要加上精确的版本号。

```
gem 'sass-rails', '~> 4.0.3'
```

```
gem 'bootstrap-sass', '~> 3.3.4'
```

```
gem 'uglifier', '>= 1.3.0'
```

```
gem 'coffee-rails', '~> 4.0.0'
```

Turbolinks, jbuilder, sdoc 用上了吗？

```
gem 'jquery-rails','3.1.2'
```

```
gem 'jquery-ui-rails', '4.0.5'
```

```
gem 'turbolinks'
```

```
gem 'jbuilder', '~> 2.0'
```

```
gem 'sdoc', '~> 0.4.0',      group: :doc
```


主谓宾？

commit ffbcbb51c73965c2aca9257a34f50a83fb8ef418

灵感，发现，管理相关的默认值，下拉框选择及搜索

Gemfile 中出现了不该出现的注释

```
# coding: utf-8
```

没有必要的注释

Prevent CSRF attacks by raising an exception.

For APIs, you may want to use :null_session inste

protect_from_forgery with: :exception

大部分的规范的使用法

- 页面中: `<%= flash[:notice] %>`,
- **controller** 中: `redirect_to, notice: '操作成功'`

不要用 `render 'new'`

`render 'new'`

要改成:

`redirect_to new_color_path`

对于 interface, 最好自定义个父类

```
class Interface::DiscoversController < ActionController::Base
```

```
class Interface::DiscoversController < BaseInterfaceController
```

将来需要对 interface 做 cache 的话:

```
class BaseInterfaceController < ActionController::Base
```

```
  cache_action /*/
```

```
end
```

json 中 ,key 与 value 最好一致

- 21 render :json => {
 :comment => " 本接口用来显示所有的发现，接收 XX
 参数 "
- 22 :all_discoveries => discoveries
- 23 items: User.all
- 24 }

两个方法之间要有空行

```
Def method1
```

```
End
```

```
Def method2
```

```
End
```


没有用的文件，删掉

- 1 # -*- encoding : utf-8 -*-
- 2 require 'test_helper'
- 3
- 4 class MaterialSortTest < ActiveSupport::TestCase
- 5 # test "the truth" do
- 6 # assert true
- 7 # end
- 8 end

下面这些文件，要删掉。留着晃眼

- 1 >File>test/
- [fu 1: test/controllers/ 1,12 All
- 1 2: test/fixtures/
- 2 3: test/helpers/
- 3 4: test/integration/
- 4 5: test/mailers/ ctiveSupport::TestCase
- 5 6: test/models/
- 6 7: test/test_helper.rb
- 7 # end

空的 helper ， 都删掉。

- app/helpers\$ cat *
- module AdminHelper
- end
- # -*- encoding : utf-8 -*-
- module ApplicationHelper
- end
- # -*- encoding : utf-8 -*-
- module BrandHelper
- end
- # -*- encoding : utf-8 -*-
- module CasesHelper
- end

单元测试大家都没写。

- 1 >File>spec/
- 1: spec/controllers/ 1,12 All
- 2: spec/factories/
- ~ 3: spec/models/
- ~ 4: spec/rails_helper.rb
- ~ 5: spec/requests/
- ~ 6: spec/spec_helper.rb